

STRAINER FOR FLANGE**CA 3241CREPINOX****APPLICATION**

General use : for water distribution and draining.

GENERAL CHARACTERISTICS

From DN50 to DN300.

For flange connection.

Mesh 6 mm

With bolting.

DIMENSIONS

DN		H	ØA	ØK	ØD	n x ØM	f	Weight (kg)
mm	inch							
50	2"	77	93	125	165	4 x Ø18	2,5	1
65	2"1/2	110	113	145	185	4 x Ø18	2,5	1,3
80	3"	125	128	160	200	4 x Ø18	2,5	1,4
100	4"	155	148	180	220	4 x Ø18	2,5	1,7
125	5"	170	178	210	250	4 x Ø18	2,5	2
150	6"	220	200	240	285	4 x Ø22	2,5	3
200	8"	300	255	295	340	4 x Ø22	2,5	4,5
250	10"	390	310	355	397	12 x Ø22	2,5	6
300	12"	410	360	410	450	12 x Ø22	2,5	7

WORKING CONDITIONS

Maximum working conditions : -20°C / +200°C

Maximum working pressure: 16 bar

STANDARDS

Fabrication according to ISO 9001 :2000

Flanged connection: ISO PN10/16 from DN50 to DN150

ISO PN16 from DN200 to DN300..

