

Ref. : CD 2140.pas

Rev. : Initial

Date : 15/12/2014

Page : 1/1

FLOW SIDE CONTROL

CD 2140



APPLICATION

Fluid flow control in piping systems.
Common use without risk of corrosion.

GENERAL CHARACTERISTIQUES

Range from DN15 to DN50.
Made of brass or bronze.
Double glass type.
With movable ball control for transparent fluids.
Not suitable for vertical pipes with upward flow.

CONSTRUCTION

7	8	Nut	Nickel-plated Steel
6	8	Screw	Nickel-plated Steel
5	1	Ball	Moplen (in option PTFE)
4	2	Glass	Tempered glass
3	2	Cover	Brass CW 617 N
2	4	Glass Gasket	Fiber
1	1	Body	Brass from DN 1/2" to DN1" Bronze from DN 1" 1/4 to DN2"
Pos.	Q-ty	Description	Material



DIMENSIONS

DN	L	H
15	95	80
20	100	90
25	107	92
32	126	112
40	137	118
50	170	140

WORKING CONDITIONS

Maximum working pressure: 16 bar.
Maximum temperature (standard ball) : +5°C / +80°C.
Fluid temperature (PTFE ball) : +5°C / +120°C

STANDARDS

Female threaded according to ISO 228.

