

Ref. : EDEBB62  
 Rev. : Initial  
 Date : 28/04/2015  
 Page : 1/1

# DIRECT CONTROL NORMALLY CLOSED SOLENOID VALVE 3/2

## EDEBB62



### APPLICATION

Fluid networks such as: water, air, inert gases, steam, fuel oil.

### GENERAL CHARACTERISTICS

Normally closed solenoid valve (NF).  
 Without differential pressure.  
 Brass body and stainless steel internal details  
 Mounting in all positions.

Voltages :  
 Alternative (24-48-110-230V)  
 Continuous (12-24-48-110 V).

### CONSTRUCTION

Pos.	Description	Material
11	Nut	Zinc plated steel
10	Washer	Zinc plated steel
9	Coil	PBT + 30% glass fiber
8	Guiding tube	Stainless steel AISI 430
7	Gasket	FPM
6	Spring	Steel
5	Plunger	Stainless steel AISI 303
4	Support	Stainless steel
3	Seal	FPM
2	Spring	Steel
1	Body	Brass CW 617 N

### DIMENSIONS

DN		A	B	C	D	Weight (kg)
mm	inch					
8	1/4"	35	84.5	47	69	0.26

### WORKING CONDITIONS

Maximum medium differential pressure:  
 10 bar (AC)  
 7 bar (DC)

Maximum medium working temperature: +150 °C  
 Ambient temperature: -10°C / +80°C

### STANDARDS

Threaded BSP gas according to ISO 228-1.

