

Ref. : JT4272 .pas

Rev. : Initial

Date : 11/10/2013

Page : 1/1

DISMANTLING JOINTS PN64

JT4272



Tecofi 
VALVE DESIGNER - FRANCE

APPLICATION

General use : for easy installation and dismantling of valves.

GENERAL CHARACTERISTICS

Range : from DN 80 up to DN 1200.
Rigid connection between the connecting pipes.
Long course.
PN64.

CONSTRUCTION

6	-	Nut	Steel-Galvanized
5	-	Stud bolt	Steel-Galvanized
4	1	Sealing ring	EPDM
3	1	Retaining flange	Steel
2	1	Flanged pipe - long	Steel
1	1	Flanged pipe - short	Steel
Pos.	Qty.	Description	Material



DIMENSIONS

DN		D2	D4	D5	L1	L2	d	N	t
mm	inch								
80	3"	98	170	215	240	390	23	8	7,0
100	4"	118	200	250	250	400	28	8	7,2
125	5"	144	240	295	250	400	31	8	7,5
150	6"	170	280	345	260	410	34	8	7,8
200	8"	222	345	415	260	410	37	12	8,4
250	10"	274	400	470	280	450	37	12	9,0
300	12"	326	460	530	280	450	37	16	9,6
350	14"	378	525	600	300	470	40	16	10,2
400	16"	429	585	670	310	510	43	16	10,8
500	20"	532	705	800	320	520	49	20	12,0
600	24"	635	820	930	350	570	56	20	13,2
700	28"	738	935	1045	370	610	56	24	14,4
800	32"	842	1050	1165	390	630	63	24	15,6
900	36"	845	1170	1285	410	640	63	28	16,8
1000	40"	1048	1290	1415	430	680	70	28	18,0
1200	48"	1255	1530	1665	490	760	78	32	20,4

STANDARDS

Flanges in accordance with ISO 2531 PN64

