

Ref. : MA 6100.pas

Rev. : C

Date : 07/01/2015

Page : 1/1

STAINLESS STEEL BOX PRESSURE GAUGE WITH DRY DIAL

MA 6100



Tecofi
VALVE DESIGNER - FRANCE

APPLICATION

For gaseous and aggressive fluids (not viscous or crystallizing liquid).

GENERAL CHARACTERISTICS

All stainless steel
Stainless steel mechanism
Dry dial (to be fitted in)
Safety glass
1 class
Protection IP65
Bottom connection BSP threaded
With vent security

CONSTRUCTION

5	1	Mechanism	Stainless steel
4	1	Dial	Aluminium
3	1	Fitting	Stainless steel 316
2	1	Needle	Aluminium
1	1	Box	Stainless steel 304
Pos.	Q-ty	Description	Material

DIMENSIONS

DN	G	H	L	L1	L2	W	D1	D2	Weight (kg)
63	1/4"	56	32	6	10.5	14	68	62	0.146
100	1/2"	90	48	14	16	22	100.8	99	0.500

WORKING CONDITIONS

Maximum temperature : 0°C / +100°C.
Working pressure range: -1 up to 60 bar
((-1+1 / 0-1.6 / 0-2.5 / 0-4 / 0-6 / 0-10 / 0-16 / 0-25 / 0-40 / 0-60 bar))

STANDARDS

Fabrication according to ISO 9001 : 2008
Designing according to EN 837-1
DIRECTIVE CEI D1 BVO : Products excluded from directive (article 3, § 3)
Threaded male BSP cylindrical ends according to ISO 228-1.

