

Ref. : RP6191BSP.pas

Rev. : Initial

Date : 18/01/2018

Page : 1/1

BSP FEMALE / FEMALE NEEDLE VALVES

RP6191BSP



APPLICATION

General use : for all kind of fluids.

GENERAL CHARACTERISTICS

From DN 1/4" to DN 1".
BSP female connections.

CONSTRUCTION

5	1	Packing	PTFE	
4	1	Packing gland	Stainless steel 316	DIN: X5CrNiMo18 10 ASTM: A182 AISI 316 BS: 970 316 S16
3	1	Stem	Stainless steel 316	DIN: X5CrNiMo18 10 ASTM: A182 AISI 316 BS: 970 316 S16
2	1	Chapeau	Stainless steel 316	DIN: X5CrNiMo18 10 ASTM: A182 AISI 316 BS: 970 316 S16
1	1	Corps	Stainless steel 316	DIN: X5CrNiMo18 10 ASTM: A182 AISI 316 BS: 970 316 S16
Pos.	Qty.	Description	Material	



DIMENSIONS

DN		L	L1	H (valve shut)	H1 (valve open)	ØD	ØD1	ØP	Weight (kg)
mm	inch								
8	1/4"	60	12	85	90	5	6	5	0,38
12	3/8"	60	12	85	90	5	6	5	0,35
15	1/2"	68	15	85	90	6	6	6	0,43
20	3/4"	75	16	95	101	8	8	8	0,65
25	1"	85	16	104	112	8	8	8	1,12

WORKING CONDITIONS

Maximum working pressure: 400 bar.
Minimum temperature : -20°C.
Maximum temperature : +180°C.

AGREEMENT AND TESTING

BSP threaded according to standard ISO 228-1.

